



Issuance date: 03.03.2025
Validity date: 03.03.2030
Validation date: 11.03.2025

Type III Environmental Product Declaration No. 761/2025



CALVERO® ACOUSTIC SCREENS



Owner of the EPD:
CALVERO Sp. z o.o. Sp.K.
Address: Katowicka 44,
42-263 Wrzosowa, Poland
Tel.: +48 34 375 80 00
Website: <https://www.calvero.pl>
Contact: biuro@calvero.pl

EPD Program Operator:
Instytut Techniki Budowlanej (ITB)
Address: Filtrowa 1,
00-611 Warsaw, Poland
Website: <http://www.itb.pl>
Contact: Michał Piasecki
energia@itb.pl

Type III Environmental Product Declaration No.761/2025



ITB is the verified member of The European Platform for EPD program operators and LCA practitioner www.eco-platform.org

BASIC INFORMATION

This declaration is the Type III Environmental Product Declaration (EPD) based on EN 15804+A2 and verified according to ISO 14025 by an external auditor. It contains the information on the impacts of the declared construction materials on the environment and their aspects verified by the independent body according to ISO 14025. Basically, comparison or evaluation of EPD data is possible only if all the compared data were created according to EN 15804+A2.

Life cycle analysis (LCA): A1-A3, C1-C4 and D modules in accordance with EN 15804
(Cradle-to-Gate with options)

The year of preparing the EPD: 2024

Product standard: EN 1090-1, EN 1090-2, ISO 3834-2

Service Life: minimum 100 years

PCR: ITB-PCR A

Declared unit: 1ton

Reasons for performing LCA: B2B

Representativeness: Polish, European, 2023

Type III Environmental Product Declaration No.761/2025

MANUFACTURER

CALVERO® started its business activity in 1994. It specializes in the supply of steel structures and transparent fillings for acoustic screens (full range of acrylic and solid polycarbonate sheets), production of ready-made acoustic panels/quarters (aluminum frame + glass), various types of aluminum panels, as well as technical consulting and optimization of technical solutions for screens.

The company's assumption is comprehensive customer service both during the implementation of the project, investment task, and after the completion of construction.

CALVERO® has specialized in its field by developing both the range of offered fillings, as well as introducing to the market a very wide range of profiles and system solutions for their mounting.

In order to meet the quality requirements for acoustic screens in Poland and Europe, CALVERO® has introduced Factory Production Control covering the process of production of acoustic screen quarters from system aluminum profiles (raw, anodized) with filling of acrylic, polycarbonate or mineral glass.

In order to be able to cooperate with all partners from Europe (especially from the EU), CALVERO® carried out tests of ready-made acoustic panels/quarters in notified Institutes in Bratislava (notified body no. 1301) and in Warsaw (ITB, notified body no. 1488), obtaining the possibility of marking its products with the CE mark.

PRODUCTS DESCRIPTION AND APPLICATION

EPD covers all range of **CALVERO® acoustic screens** (acrylic, polycarbonate, wool sheets).
Maximum weight of shipping item: 1 ton. The structures are made of the profiles made of aluminium.

Table 1. An average composition of aluminium acoustic screen manufactured by **CALVERO®** according to the list of production materials

Component	Contribution (mass based)
Aluminium	50%
Core materials (i.a. stone wool, PMMA/PC boards)	50%
Anticorrosive coverings/paint	<0.1%

Type III Environmental Product Declaration No.761/2025

LIFE CYCLE ASSESSMENT (LCA) – general rules applied

Unit

The declared unit is 1 m² of product.

System boundary

The life cycle analysis of the declared products covers "Product Stage" A1-A3, C1-C4+D modules in accordance with EN 15804+A2 and ITB PCR A (cradle to gate with options). Energy and water consumption, emissions as well as information on generated wastes were inventoried and were included in the calculation. It can be assumed that the total sum of omitted processes does not exceed 5% of all impact categories. In accordance with EN 15804+A2, machines and facilities (capital goods) required for the production as well as transportation of employees were not included in LCA.

Allocation

The allocation rules used for this EPD are based on general ITB's document PCR A. In the aggregated module A1-A3, material losses in the assembly of the products in the factory are defined on the averaged specific values for the site. Input and output data from the production is inventoried and allocated to the production on the mass basis. The declaration covers a wide range of aluminium/wool/PMMA/PC products. Their production resources and processing stages are basically similar, so it is possible to average the production by product weight so production is averaged for all products. Avoided burden approach is applied in the use of recycled and/or secondary raw materials, as well as loads and benefits beyond the system boundary from material recycling. No loads and benefits beyond the system boundary from energy recovery from the end of life of the product or packaging is included.

System limits

In the assessment, all available data from production have been considered, i.e. all raw materials/elements used as per assembly process, utilized thermal energy, and electric power consumption. Thus material and energy flows contributing less than 1 % of mass or energy have been considered. It can be assumed that the total sum of neglected processes does not exceed 5 % of energy usage and mass per module A, B, C or D. Machines and facilities required during production are neglected. The production of etiquettes, tape and glue was also not considered.

Modules A1 and A2: Raw materials supply and transport


Aluminium semi-finished products used for the production of the aluminium structures comes from various aluminium production plants. Ancillary materials such as chemicals used for production purposes, packaging materials come from local Polish suppliers. Data on transport of the different products to the manufacturing plants is collected and modelled for factory by assessor. The aluminium used comes from domestic suppliers.. Data on transport of the different products to the manufacturing plants is collected and modelled for factory by assessor. Module A2 (transport) includes truck transport and uses European averages for fuel data

Module A3: Production

At the beginning of the production process, the required metal materials are collected, such as: Rolled sheets. Aluminium semi-finished products are subjected to cutting, marking, drilling and bending. the component undergoes operations providing the proper quality of its edges and is assembled and welded according to a project. In the next steps structure is painted and marked. The production processes carried out at CALVERO® are shown in Figure 1.

Type III Environmental Product Declaration No.761/2025

Figure 1. A basic scheme of CALVERO® acoustic screen product manufacturing process.



Type III Environmental Product Declaration No.761/2025

Modules C1-C4 and D: End-of-life (EOL)

Due to the fact that the declaration covers a wide range of aluminium acoustic screens and usage scenarios, it is not possible to directly specify the de-construction technology and the amount of energy for disassembly in C1 module (so this module is very generic based on literature). In the adapted end-of-life scenario, the de-constructed steel products are transported to a steel mill distant by 30 km on > 16t lorry EURO 4 where are used as steel scrap to produce a new steel. The recycling potential of C3 module is 70% and it is assumed that 30% of the products will end up in a landfill – C4 module (Table 2). Module D presents credits resulting from the recycling of the steel scrap (used for steel production), calculated in accordance with the approach developed by World Steel Association.

Table 2. End-of-life scenario for the steel structures Material Material recovery Recycling Landfilling Steel scrap 100% 98% 2%.

Table 2. End-of-life scenario for the product components.

Material	Material recovery [%]	Recycling [%]	Landfilling [%]
Aluminium scrap	100	98	2
Stone wool insulation board	100	98	2
PMMA board	100	98	2
Polycarbonate board	100	98	2
Mineral glass	100	98	2

Electricity at end-of-life (module C) has been modelled using an average European electricity mix as the location where the product reaches end-of-life is unknown.

Data collection period

The data for manufacture of the declared products refer to period between 01.01.2023 – 31.12.2023 (1 year). The life cycle assessments were prepared for Poland and Europe as reference area.

Data quality

The data selected for LCA originate from ITB-LCI questionnaires completed by **CALVERO®** and verified during data audit. No data collected is older than five years and no generic datasets used are older than ten years. The representativeness, completeness, reliability, and consistency is judged as good. The background data for the processes come from the following resources database Ecoinvent v.3.9.1 and specific suppliers. Specific (LCI) data quality analysis was a part of the input data verification.

Assumptions and estimates

The impacts of the representative of the products were aggregated using weighted average.

Calculation rules

LCA was performed using openLCA tool developed in accordance with EN15804+A2. Emission of greenhouse gases was calculated using the IPCC 2021 GWP method with a 100-year horizon. Emission of acidifying substances, Emission of substances to water contributing to oxygen depletion, Emission of gases that contribute to the creation of ground-level ozone, Abiotic depletion, and ozone depletion emissions where all calculated with the CML-IA baseline method.

Additional information

Polish electricity (Ecoinvent v 3.10 supplemented by actual national KOBIZE data) emission factor used is 0.698 kg CO2/kWh. As a general rule, no particular environmental or health protection measures other than those specified by law are necessary.

Type III Environmental Product Declaration No.761/2025

LIFE CYCLE ASSESSMENT (LCA) – Results

Declared unit

The declaration refers to declared unit (DU) – 1 m² of the products manufactured by **CALVERO®**. The following life cycle modules (table 3) were included in the analysis.

Table 3. System boundaries for the environmental characteristic of the product.

Environmental assessment information (MD – Module Declared, MND – Module Not Declared, INA – Indicator Not Assessed)																
Product stage			Construction process		Use stage							End of life				Benefits and loads beyond the system boundary
Raw material supply	Transport	Manufacturing	Transport to construction site	Construction-installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse-recovery-recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
MD	MD	MD	MND	MND	MND	MND	MND	MND	MND	MND	MND	MD	MD	MD	MD	MD

The declaration refers to declared unit (DU) – 1 m² of the acoustic screen produced **CALVERO®**.

The following life cycle modules (Table 3) were included in the analysis.

The following tables 4-7 show the environmental impacts of the life cycle of selected modules (A1-A3+C1-C4+D).

Type III Environmental Product Declaration No.761/2025

Table 4. Life cycle assessment (LCA) results of the steel product – environmental impacts (DU: 1 m²).

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Global Warming Potential	eq. kg CO ₂	1.70E+02	6.33E-01	8.05E-02	7.96E+01	2.93E-01	-7.66E+01
Greenhouse potential - fossil	eq. kg CO ₂	1.72E+02	6.29E-01	8.04E-02	7.80E+01	2.90E-01	-7.50E+01
Greenhouse potential - biogenic	eq. kg CO ₂	-4.33E+00	3.44E-03	7.08E-05	4.09E-01	3.08E-03	-3.89E-01
Global warming potential - land use and land use change	eq. kg CO ₂	2.84E+00	1.90E-04	3.93E-05	1.24E+00	3.10E-04	-1.23E+00
Stratospheric ozone depletion potential	eq. kg CFC 11	5.03E-05	2.62E-09	1.76E-09	2.07E-06	3.33E-09	-2.03E-06
Soil and water acidification potential	eq. mol H ⁺	1.20E+00	4.51E-03	3.30E-04	4.99E-01	1.85E-03	-4.72E-01
Eutrophication potential - freshwater	eq. kg P	7.36E-02	7.60E-04	5.66E-06	3.33E-02	8.54E-05	-3.30E-02
Eutrophication potential - seawater	eq. kg N	8.58E-01	6.50E-04	1.30E-04	7.16E-02	4.80E-04	-6.67E-02
Eutrophication potential - terrestrial	eq. mol N	1.76E+00	5.67E-03	1.36E-03	6.87E-01	5.11E-03	-6.29E-01
Potential for photochemical ozone synthesis	eq. kg NMVOC	7.30E-01	1.64E-03	4.90E-04	2.94E-01	1.69E-03	-2.78E-01
Potential for depletion of abiotic resources - non-fossil resources	eq. kg Sb	1.65E-03	2.05E-07	2.66E-07	2.00E-04	6.19E-07	-1.80E-04
Abiotic depletion potential - fossil fuels	MJ	2.31E+03	7.21E+00	1.16E+00	1.21E+03	4.17E+00	-1.18E+03
Water deprivation potential	eq. m ³	1.51E+02	1.35E-01	5.67E-03	1.09E+02	5.14E-02	-1.09E+02

Type III Environmental Product Declaration No.761/2025

Table 5. Life cycle assessment (LCA) results of the steel product – environmental impacts (DU: 1 m²).

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Particulate matter	disease incidence	1.59E-05	7.46E-09	6.59E-09	5.45E-06	2.87E-08	-5.11E-06
Potential human exposure efficiency relative to U235	eg. kBq U235	3.52E+01	2.07E-02	1.54E-03	1.45E+01	1.81E-02	-1.45E+01
Potential comparative toxic unit for ecosystems	CTUe	3.80E+03	1.77E+00	5.66E-01	4.78E+02	6.12E+01	-4.51E+02
Potential comparative toxic unit for humans (cancer effects)	CTUh	3.40E-07	2.27E-10	3.69E-11	1.90E-07	2.62E-10	-1.89E-07
Potential comparative toxic unit for humans (non-cancer effects)	CTUh	3.56E-06	1.01E-08	8.14E-10	1.67E-06	3.43E-09	-1.65E-06
Potential soil quality index	dimensionless	1.28E+03	1.52E+00	6.83E-01	9.06E+01	5.09E+00	-8.04E+01

Type III Environmental Product Declaration No.761/2025

Table 6. Life cycle assessment (LCA) results of the steel product – environmental impacts (DU: 1 m²).

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Consumption of renewable primary energy - excluding renewable primary energy sources used as raw materials	MJ	5.29E+02	6.66E-01	1.78E-02	3.32E+02	2.79E-01	-3.31E+02
Consumption of renewable primary energy resources used as raw materials	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total consumption of renewable primary energy resources	MJ	5.29E+02	6.66E-01	1.78E-02	3.32E+02	2.79E-01	-3.31E+02
Consumption of non-renewable primary energy - excluding renewable primary energy sources used as raw materials	MJ	2.24E+03	7.16E+00	1.06E+00	1.17E+03	3.95E+00	-1.15E+03
Consumption of non-renewable primary energy resources used as raw materials	MJ	7.10E+01	4.96E-02	1.00E-01	3.81E+01	2.16E-01	-3.62E+01
Total consumption of non-renewable primary energy resources	MJ	2.31E+03	7.21E+00	1.16E+00	1.21E+03	4.17E+00	-1.18E+03
Consumption of secondary materials	kg	1.03E+01	3.90E-02	1.25E-03	8.52E-01	7.18E-03	-8.75E-01
Consumption of renew. secondary fuels	MJ	2.01E+00	2.24E-02	3.40E-04	3.18E-01	2.26E-03	-3.39E-01
Consumption of non-renewable secondary fuels	MJ	4.81E+00	7.47E-02	6.60E-04	5.69E-01	8.39E-03	-5.12E-01
Net consumption of freshwater	m ³	3.29E+00	1.92E-02	1.40E-04	2.40E+00	3.04E-03	-2.39E+00

Type III Environmental Product Declaration No.761/2025

Table 7. Life cycle assessment (LCA) results of the steel product – environmental impacts (DU: 1 m²).

Type III Environmental Product Declaration No. 761/2025

Verification

The process of verification of this EPD is in accordance with ISO 14025 and ISO 21930. After verification, this EPD is valid for a 5-year-period. EPD does not have to be recalculated after 5 years, if the underlying data have not changed significantly.

The basis for LCA analysis was EN 15804 and ITB PCR A	
Independent verification corresponding to ISO 14025 (sub clause 8.1.3.)	
<input checked="" type="checkbox"/> external	<input type="checkbox"/> internal
Verification of EPD: Michał Piasecki, PhD., D.Sc., Eng.	
LCA, LCI audit and input data verification: Bartosz Żymańczyk, BEng	
LCA verification: Filip Poznański, M.Sc. eng.	

Note 1: The declaration owner has the sole ownership, liability, and responsibility for the information provided and contained in EPD. Declarations of construction products may not be comparable if they do not comply with EN 15804+A2. For further information about comparability, see EN 15804+A2 and ISO 14025.

Note 2: ITB is a public Research Organization and Notified Body (EC Reg. no 1488) to the European Commission and to other Member States of the European Union designated for the tasks concerning the assessment of building products' performance. ITB acts as the independent, third-party verification organization (ISO 17025/17065/17029). ITB-EPD program is recognized and registered member of The European Platform - Association of EPD program operators and ITB-EPD declarations are registered and stored in the international ECO-PORTAL.

Normative references

- ITB PCR A General Product Category Rules for Construction Products
- EN 1090-2:2018 - Execution of steel structures and aluminium structures - Technical requirements for steel structures
- ISO 14025:2006, Environmental labels and declarations – Type III environmental declarations – Principles and procedures
- ISO 21930:2017 Sustainability in buildings and civil engineering works – Core rules for environmental product declarations of construction products and services
- ISO 14044:2006 Environmental management – Life cycle assessment – Requirements and guidelines
- ISO 15686-1:2011 Buildings and constructed assets – Service life planning – Part 1: General principles and framework
- ISO 15686-8:2008 Buildings and constructed assets – Service life planning – Part 8: Reference service life and service-life estimation
- EN 15804:2012+A2:2019 Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products
- ISO 14067:2018 Greenhouse gases — Carbon footprint of products — Requirements and guidelines for quantification
- PN-EN 15942:2012 Sustainability of construction works – Environmental product declarations – Communication format business-to-business
- KOBiZE Wskaźniki emisjyjności CO₂, SO₂, NO_x, CO i pyłu całkowitego dla energii elektrycznej. Grudzień 2023
- World Steel Association 2017 Life Cycle inventory methodology report for steel products

Michał Piasecki, PhD. D.Sc.

Qualified electronic signature

Type III Environmental Product Declaration No. 761/2025



Instytut Techniki Budowlanej

00-611 Warsaw, Filtrowa 1

Thermal Physics, Acoustics and Environment Department
02-656 Warsaw, Ksawerów 21

CERTIFICATE № 761/2025

of TYPE III ENVIRONMENTAL DECLARATION

Products:

CALVERO® ACOUSTIC SCREENS

Manufacturer:

CALVERO Sp. z o.o. Sp.K.
Katowicka 44, 42-263 Wrzosowa, Poland

confirms the correctness of the data included in the development of
Type III Environmental Declaration and accordance with the requirements of the standard

EN 15804+A2

**Sustainability of construction works.
Environmental product declarations.**

Core rules for the product category of construction products.


This certificate, issued on 29th January 2025 is valid for 5 years
or until amendment of mentioned Environmental Declaration

Head of the Thermal Physic, Acoustics
and Environment Department


Agnieszka Winkler-Skalna, PhD



Deputy Director
for Research and Innovation


Krzysztof Kuczyński, PhD

Warsaw, January 2025